

LEXRON

8KW - 11KW MPPT INVERTER DATASHEET



Model	GA11048MH	GA11048MH
AC Voltage Range	230VAC	230VAC
Selectable Voltage Range	180-260VAC	180-260VAC
Frequency Range	50Hz / 60Hz	50Hz / 60Hz
Efficiency (Peak)	%98	%98
Surge Power	16000VA	22000VA
Battery Voltage	48VDC	48VDC
Transfer Time	≤10ms (UPS Mode) / ≤20ms (INV Mode)	≤10ms (UPS Mode) / ≤20ms (INV Mode)
Maximum Pv input Power	9000W	2x7500W
Maximum Pv input Current	27A	27+27A
Maximum AC Charge Current	100A	100A
Maximum Solar Charge Current	120A	160A (80+80)
Max. PV Array (Open Circuit Voltage)	500VDC	500VDC (DOUBLE MPPT)
MPPT Tracking Range(Vmp)	120~500VDC	120~500VDC (DOUBLE MPPT)
Dimension, D x W x H (mm)	440x335x138mm	571x500x149mm
Net Weight (kg)	10,7kg	19,5kg
Paralel Kit	NO	YES
Battery Type	External lead acid battery or water battery, or lithium battery	

Pure sine wave inverter

- Selectable input voltage range for home appliances and personal computers
- Support Working without Battery: Reduce Solar System Cost
- Parallel Function Up to Maximum 9 Units: Enlarge More Loads
- Selectable charging current based on applications
- Configurable AC/Solar input priority via LCD setting
- Compatible to AC mains or generator power
- Battery equalization for optimized battery performance and lifecycle
- BMS function for lithium battery
- Lithium Battery Auto-restart Function, More Convenient for Lithium Battery Charging

ENVIRONMENT

Humidity	5% to 95% Relative Humidity (Non - condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C

LEXRON

ACS Enerji
Yaşanabilir Bir Dünya için Üretiyoruz

ACS ENERJİ

İTOB OSB Mah. Ekrem Demirtaş Cad. No: 44
Menderes - İZMİR

0232 799 00 98

www.acsenerji.com